# iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK


### Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6-S-1478-840M-DAD-MP-FWED 97-IL600243ED Surface Mount Surface Office, General and Retail

#### **Specification text**

Surface Mount luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 3039lm with an efficacy of 117lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in White.



### Lighting performance


Output lumens:	3039 lm
Efficacy:	117 lm/W
Rated power:	23 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







## lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.