# iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

| Product reference: |
|--------------------|
| Article Number:    |
| Product type:      |
| Mounting type:     |
| Applications:      |

IL6-S-1478-830M-DAD-OP-FGED 97-IL600248ED Surface Mount Surface Office, General and Retail

#### **Specification text**

Surface Mount luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3199.06lm with an efficacy of 123lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.



### Lighting performance

| Output lumens:                | 3199.06 lm  |
|-------------------------------|-------------|
| Efficacy:                     | 123 lm/W    |
| Rated power:                  | 23 W        |
| Control gear:                 | DALI        |
| Dimming range:                | 1-100%      |
| DC Suitable:                  | Yes         |
| Colour temperature:           | 3000 K      |
| MacAdams                      | < 3         |
| CRI:                          | 85          |
| Radiation pattern:            | Symmetrical |
| Beam angle:                   | Wide        |
| Unified glare rating (U.G.R): | <22         |
|                               |             |


#### **Physical details**

| Finish:    |  |  |
|------------|--|--|
| Length:    |  |  |
| Width:     |  |  |
| Height:    |  |  |
| IP Rating: |  |  |
|            |  |  |



Grey





# lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.