iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-R-1494-830M-DAD-MP-FGE 97-IL600322E Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 2947.83Im with an efficacy of 114lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1494 x W76 x H76.5mm. Finished in Grey.

2947.83 lm 114 lm/W 0 W DALI 1-100% Yes 3000 K < 3 85

Symmetrical Wide <19




Lighting performance

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

Grey 1494 mm 76 mm 76.5 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.