# iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

### Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6-R-1494-840M-DAD-OP-FB 97-IL600330 Recessed Recessed Office, General and Retail

#### **Specification text**

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3298lm with an efficacy of 127lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1494 x W76 x H76.5mm. Finished in Black.

> 3298 lm 127 lm/W 0 W DALI 1-100% Yes 4000 K < 3 85



# Lighting performance

Output lumens:
Efficacy:
,
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):
Beam angle:


#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		

## Black 1494 mm 76 mm 76.5 mm IP20

Symmetrical Wide <22





# lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.