iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type


Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1968-830M-DADI-MP-FWES 97-IL600401ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 6205.09lm with an efficacy of 126lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1968 x W60 x H80mm. Finished in White.

6205.09 lm 126 lm/W 61.7 W DALI 1-100% Yes 3000 K < 3 85

Symmetrical Wide <19





Lighting performance

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

White 1968 mm 60 mm 80 mm IP20







RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.