iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1968-840M-DADI-OP-FGES 97-IL600418ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 6742lm with an efficacy of 136lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1968 x W60 x H80mm. Finished in Grey.




Lighting performance


Output lumens:	6742 lm
Efficacy:	136 lm/W
Rated power:	61.7 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.