iline 6

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

| Product reference: | | |
|--------------------|--|--|
| Article Number: | | |
| Product type: | | |
| Mounting type: | | |
| Applications: | | |

IL6-R-1984-840M-DAD-MP-FGES 97-IL600525ES Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4052lm with an efficacy of 117lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1984 x W76 x H76.5mm. Finished in Grey.



Lighting performance


| Output lumens: | 4052 lm |
|-------------------------------|-------------|
| Efficacy: | 117 lm/W |
| Rated power: | 0 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 4000 K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | <19 |
| | |

Physical details

| Finish: | Grey |
|------------|---------|
| Length: | 1984 mm |
| Width: | 76 mm |
| Height: | 76.5 mm |
| IP Rating: | IP20 |
| | |







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.