# iline pro 6

- ( +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK


## Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6P-WS-1144-830M-DADI-MP-FGE 97-IL6P0003E Pendant Pendant Office, General and Retail

# **Specification text**

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4889Im with an efficacy of 137Im/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1144 x W65 x H90mm. Finished in Grey.




## Lighting performance


Output lumens:	4889 lm
Efficacy:	137 lm/W
Rated power:	35.6 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.