iline pro 6

- (+44 (0) 1279 450882
- () WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL6P-WS-1144-835M-DADI-OP-FGED 97-IL6P0015ED Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4911lm with an efficacy of 138lm/W. Light source colour temperature 3500K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1144 x W65 x H90mm. Finished in Grey.




Lighting performance


Output lumens:	4911 lm	
Efficacy:	138 lm/W	
Rated power:	35.6 W	
Control gear:	DALI	
Dimming range:	1-100%	
DC Suitable:	Yes	
Colour temperature:	3500 K	
MacAdams	< 3	
CRI:	85	
Radiation pattern:	Symmetrical	
Beam angle:	Wide	
Unified glare rating (U.G.R):	<22	

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.