# iline pro 6

- +44(0)1279 450882
- ( WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

### Luminaire type

Product reference: IL6P-WS-1144-840M-DADI-OP-FGED

Article Number: 97-IL6P0018ED
Product type: Pendant
Mounting type: Pendant

Applications: Office, General and Retail

#### **Specification text**


Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4986lm with an efficacy of 140lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1144 x W65 x H90mm. Finished in Grey.



## Lighting performance

4986 lm Output lumens: 140 lm/W Efficacy: Rated power: 35.6 W Control gear: DALI Dimming range: 1-100% DC Suitable: Yes Colour temperature: 4000 K < 3 MacAdams 85 CRI:

Radiation pattern: Symmetrical Beam angle: Wide
Unified glare rating (U.G.R): <22



## **Physical details**

 Finish:
 Grey

 Length:
 1144 mm

 Width:
 65 mm

 Height:
 90 mm

 IP Rating:
 IP20

