# iline pro 6

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

### Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6P-S-1144-830M-DAD-MP-FWES 97-IL6P0037ES Surface Mount Surface Office, General and Retail

## **Specification text**

Surface Mount luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 2378lm with an efficacy of 135lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1144 x W65 x H90mm. Finished in White.



## Lighting performance


Output lumens:	2378 lm
Efficacy:	135 lm/W
Rated power:	17.65 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

### **Physical details**

Finish:
Length:
Width:
Height:
IP Rating:

## White 1144 mm 65 mm 90 mm IP20







The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.