iline pro 6

- (+44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:		
Article Number:		
Product type:		
Mounting type:		
Applications:		

IL6P-WS-1494-835M-DADI-MP-FBES 97-IL6P0205ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 6324lm with an efficacy of 136lm/W. Light source colour temperature 3500K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1494 x W65 x H90mm. Finished in Black.




Lighting performance


Output lumens:	6324 lm
Efficacy:	136 lm/W
Rated power:	46.5 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3500 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Black 1494 mm 65 mm 90 mm IP20







The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.