# iline pro 6

- ( +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

# Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6P-WS-1494-830M-DADI-OP-FGES 97-IL6P0212ES Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 6316lm with an efficacy of 136lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1494 x W65 x H90mm. Finished in Grey.




### Lighting performance


Output lumens:	6316 lm
Efficacy:	136 lm/W
Rated power:	46.5 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

#### **Physical details**

Finish:		
Length:		
Width:		
Height:		
IP Rating:		









The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.