# iline pro 6

- ( +44 (0) 1279 450882
- () WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK


#### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL6P-WS-1494-840M-DAD-MP-FG 97-IL6P0227 Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 3202lm with an efficacy of 139lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1494 x W65 x H90mm. Finished in Grey.




## Lighting performance


Output lumens:	3202 lm
Efficacy:	139 lm/W
Rated power:	23 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

#### **Physical details**

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

# Grey 1494 mm 65 mm 90 mm IP20





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.