iline pro 6

- (+44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK


Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6P-WS-14984-830M-DAD-OP-FGES 97-IL6P0230ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3038lm with an efficacy of 132lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1494 x W65 x H90mm. Finished in Grey.




Lighting performance


Output lumens:	3038 lm
Efficacy:	132 lm/W
Rated power:	23 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:		
Length:		
Width:		
Height:		
IP Rating:		







lightworks RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.