# iline pro 6

( +44 (0) 1279 450882

() WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

#### Luminaire type


Product reference: Article Number: Product type: Mounting type: Applications:

IL6P-WS-1984-835M-DADI-MP-FBED 97-IL6P0405ED Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 8398lm with an efficacy of 136lm/W. Light source colour temperature 3500K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1984 x W65 x H90mm. Finished in Black.

> 8398 lm 136 lm/W 61.7 W DALI 1-100% Yes 3500 K < 3 85



## Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


#### **Physical details**

Finish:
Length:
Width:
Height:
IP Rating:

## Black 1984 mm 65 mm 90 mm IP20

Symmetrical Wide <19





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.