iline pro 6

(+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

- SALES@RIDI.CO.UK

Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6P-WS-1984-835M-DADI-MP-FGES 97-IL6P0406ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline PRO 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 8610lm with an efficacy of 140lm/W. Light source colour temperature 3500K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1984 x W65 x H90mm. Finished in Grey.

> 8610 lm 140 lm/W 61.7 W DALI 1-100% Yes 3500 K < 3 85



Lighting performance


Output lumens:
Efficacy:
Rated power:
Control gear:
Dimming range:
DC Suitable:
Colour temperature:
MacAdams
CRI:
Radiation pattern:
Beam angle:
Unified glare rating (U.G.R):


Physical details

Finish:	
Length:	
Width:	
Height:	
IP Rating:	

Grey 1984 mm 65 mm 90 mm IP20

Symmetrical Wide <19





lightworks

RIDI

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 21/03/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.