

KOALA

RIDI UK

Additions by Avolux

+44 (0) 1279 450882
WWW.RIDI.CO.UK
SALES@RIDI.CO.UK

Luminaire type

Product reference:	KOALA-830-S-ND-SW
Article Number:	97-KOA0152
Product type:	Wall Light
Mounting type:	Wall Mounted
Applications:	Exterior

Specification text

Wall Light luminaire from the KOALA family. Direct Indirect, Narrow lighting distribution, UGR N/A. Light output of 10670lm with an efficacy of 133.4 lm/W. Light source colour temperature 3000K and CRI 80. Complete with Fixed Output control gear. Nominal dimensions L200mm x W150mm x H365mm. Finished in Black.



Lighting performance

Output lumens:	10670 lm
Efficacy:	133.4 lm/W
Rated power:	80 W
Control gear:	Fixed Output
Dimming range:	0
DC Suitable:	No
Colour temperature:	3000K
MacAdams	<3
CRI:	80
Radiation pattern:	Direct Indirect
Beam angle:	Narrow
Unified glare rating (U.G.R.):	N/A



Physical details

Finish:	Black
Width:	150mm
Depth:	200mm
Height:	365mm
Protection Rating (IP):	IP65
Impact Rating (IK):	IK08

